

WOLF CORS 10W-30 FE

02/03/2026
3501

High performance ACEA E11 / API CK-4 formulation specifically developed for the lubrication of equipment used in construction, agriculture and public works machines. It offers outstanding fuel saving and covers a wide set of applications such as engines, hydraulic systems, wet brakes, manual and powershift transmissions.

APPLICATIONS

Engine application: This oil is advised for the lubrication of heavy duty diesel engines and vehicles with and without particulate filter, it meets the requirements of the latest engine technologies with emission control systems Stage IIIB, Stage IV Final and Tier 4i, Tier 4 Final, as well as older generations (Stage I, II, IIIA, Tier 1, 2, 3). Gearboxes, powershift or manual, power take-off. Hydraulic systems of agricultural tractors and off-highway equipment. Wet brakes.

FEATURES

Anti-wear and oxidation stability: proven protection of critical parts
Cold start: excellent fluidity at low temperature

SPECIFICATIONS

ACEA	A3/B4	CASE	Tier 4F engines
ACEA	E11	CATERPILLAR	ECF-3/ECF-2/ECF-1a
ACEA	E3	CATERPILLAR	HYDO ADVANCED 10/30
ACEA	E9-16/E7/E5	CATERPILLAR	HYDO ADVANCED 10W, 20-30
AFNOR	NF E 68-603 E	CATERPILLAR	MTO
API	CG-4	CATERPILLAR	SATO
API	CJ-4/CI-4 Plus/CI-4/CH-4	CATERPILLAR	TO-2
API	CK-4	CATERPILLAR	TO-4 (SAE10W,30)
API	GL-4/SAE30	CATERPILLAR	TO-4M (SAE 10W30)
API	GL-5 (Low speed/high torque)	CUMMINS	CES 20086/81/78/77/76
API	SF/CE	DAF	PSQL 2.1 E
API	SN	DANA	GEARBOXES
DIN	51524 T3 HVLPD	DETROIT DIESEL	DFS 93K215
ISO	VG 46(After 100h)/HV	DETROIT DIESEL	DFS 93K218
JASO	DH-1/DH-2	DETROIT DIESEL	DFS 93K222
JCMA	HK 46W(extend.drain)	DEUTZ	approval DQC-III-18 LA
ALLISON	C4 (Agriculture applic.)	DEUTZ	DQC-III-10/10LA
ALLISON	TES 439	DEUTZ	TTCD
CASE	MAT 3509	DTRF	15B110
CASE	MAT 3525	DTRF	approval 15C100
CASE	MAT 3526	EATON VICKERS	I-280-S
CASE	MAT 3571	EATON VICKERS	M-2950-S
CASE	MAT 3572	EATON	GEARBOXES
CASE	MAT 3622	FORD	ESN-M2C134 C/D
CASE	MS1230	FORD	ESN-M2C159 B/C

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



FORD	FNH 82009201	MB	228.3
FORD	WSS-M2C171-F1	MB	228.31
GLOBAL	DHD-1	MF	M 1135
HITACHI	Tier 4F engines	MF	M 1139
JCB	Standard 4000/2500	MF	M 1143
JCMA	HK VG46L (Japan.OEM's)	MF	M 1144
JD	J20C	MF	M 1145
JD	J27	MTU	Oil Category 2 / 2.1
JD	JDQ-78X	NH	NH 030C
KOMATSU	CLUTCH: TO-10,30	NH	NH 410B
KOMATSU	GEARBOXES	NH	NH 420A
KOMATSU	HO-46 (HV)	PERKINS	Tier 4F engines
KOMATSU	H056-HE	RENAULT	approval RLD-3
KOMATSU	HO-MVK	RENAULT	RGD
KOMATSU	KES 07.851.2	RENAULT	RLD
KOMATSU	KES 07.868.1	RENAULT	RLD-2
KOMATSU	MICRO CLUTCH TEST (JCMAS)	RENAULT	RLD-4
KOMATSU	Tier 4F engines	RENAULT	RXD
LIEBHERR	Hydraulic Systems	Sauer Sunstrand/Danfoss	Hydro Static Trans Fluid
LIEBHERR	Tier 4F engines	VOLVO	approval VDS-4.5
MACK	approval EO-S 4.5	VOLVO	VDS-3/VDS-4
MACK	EO-M PLUS	ZF	TE-ML 03A
MACK	EO-N	ZF	TE-ML 05K
MACK	EO-N Premium Plus	ZF	TE-ML 06A
MACK	EO-O Premium Plus	ZF	TE-ML 06B
MAN	271	ZF	TE-ML 06C
MAN	M3275-1/M3575	ZF	TE-ML 07B
MAN	M3775	ZF	TE-ML 07D
MB	227.1		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	74.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.9
Viscosity index	ASTM D2270		157
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfub.com

