

GEAR OIL

GL 1, GL 3 SAE 140

This is a lubricant for gearboxes and rear axles with conical teeth or screw type. This oil is made with highly refined base oils containing anti-wear additives and an additive to lower the pour point.

APPLICATIONS

It can be used in manual gearboxes and rear axles where oils of API GL level 1&3 are prescribed, e.g. in most Fiat-Iveco or Volvo trucks and also in Fuller gearboxes.

FEATURES

- Extended oil life: proven resistance to oil degradation

PERFORMANCE PROFILE

SPECIFICATIONS

API - GL-1

API - GL-3

VOLVO - 97305

TYPICAL CHARACTERISTICS

| TEST | METHOD | UNIT | AVERAGE RESULTS |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.902 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 387 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 27.3 |
| Viscosity index | ASTM D2270 | | 96 |
| Pour point | ASTM D6892 | °C | -18 |
| Flash Point COC | ASTM D92 | °C | 230 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.