The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF RACING TRANS 75W-90 ESTER

This advanced full synthetic PAO based transmission oil with ester for racing vehicles has a very high viscosity index. The oil's excellent viscosity at low temperatures guarantees quick protection of all gears. It is blue colored.

APPLICATIONS

This is a special transmission oil with extreme pressure properties, specifically composed for use in extreme racing circumstances.

FEATURES

Frictional properties: very smooth gear shifting, no vibration.

Anti-wear protection: extended transmission life.

Extended oil life: superior thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	SADEV	SFU
API	MT-1	SCHMIDT	SFU
ARVIN MERITOR	0-76-E	ANTRIEBSTECHNIK	
BMW	OSP	X-TRAC	SFU
CHRYSLER	MS 9763	ZF	TE-ML 05A
HEWLAND	SFU	ZF	TE-ML 05B
HOLLINGER	SFU	ZF	TE-ML 07A
MACK	GO-J	ZF	TE-ML 12N
MCLAREN	MOB PTX	ZF	TE-ML 16F
PORSCHE	999.917.062.00	ZF	TE-ML 17B
PORSCHE	999.917.067.00	ZF	TE-ML 19C
PORSCHE	999.917.090.00	ZF	TE-ML 21A

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm²/s	105
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.5
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

