

WOLF OFFICIALTECH 5W40 UHPD S

14/04/2025
15707

This is a synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with after treatment systems.

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO VI standard, TIER IV interim, TIER IV final, TIER V, stage IIIB, stage IV, stage V. It specifically includes the Chrysler MS 10902 application.

FEATURES

SPECIFICATIONS

ACEA	E11	DTFR	15C110
ACEA	E6-16	DTFR	15C120
ACEA	E7	FORD	WSS-M2C171-E
ACEA	E8	FORD	WSS-M2C171-F1
ACEA	E9-16	IVECO	18-1804 Classe T2 E7
API	CI-4	IVECO	18-1804 Classe TLS E9
API	CI-4 Plus	JCB	Standard 4001/2700
API	CJ-4	JD	JDQ-78X
API	CK-4	LIEBHERR	LH-00-ENG5C LA
API	SN	MACK	EO-M PLUS
JASO	DH-1	MACK	EO-N
JASO	DH-2	MACK	EO-N Premium Plus
ALLISON	C4	MACK	EO-O Premium Plus
CATERPILLAR	ECF-1a	MACK	EO-S 4.5
CATERPILLAR	ECF-2	MAN	M3271-1
CATERPILLAR	ECF-3	MAN	M3477
CATERPILLAR	TO-2	MAN	M3575
CHRYSLER	MS 10902	MAN	M3775
CUMMINS	CES 20076	MB	235.28
CUMMINS	CES 20077	MTU	Oil Category 2.1
CUMMINS	CES 20078	MTU	Oil Category 3.1
CUMMINS	CES 20081	RENAULT	RGD
CUMMINS	CES 20086	RENAULT	RLD
CUMMINS	CES 20092	RENAULT	RLD-2
DAF	EXTENDED DRAIN	RENAULT	RLD-3
DETROIT DIESEL	DFS 93K215	RENAULT	RLD-4
DETROIT DIESEL	DFS 93K218	RENAULT	RXD
DETROIT DIESEL	DFS 93K222	SCANIA	LA
DEUTZ	DQC IV-10 LA	VOITH	Retarder Oil Class B
DEUTZ	DQC-III-10 LA	VOLVO	VDS-3
DEUTZ	DQC-III-18 LA	VOLVO	VDS-4
DEUTZ	DQC-IV-18 LA	VOLVO	VDS-4.5
DTFR	13D110		
DTFR	15C100		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm²/s	84.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.9
Viscosity index	ASTM D2270		170
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

