# CHAMPION COOLANT ASIAN LL -36°C

High-performing ready-to-use coolant based on ethylene glycol with state-of-the-art P-OAT corrosion protection technology, for modern high performance engines. With the P-OAT technology, organic acids work together with with mineral inhibitors for the best possible protection.

## **APPLICATIONS**

This P-OAT coolant is especially developed for the protection of modern combustion engines cooling systems present in Asian OEM's.

It is basically miscible with most OAT MEG based coolants but for the best possible corrosion protection we recommend to use only this P-OAT coolant for long-term protection.

## **FEATURES**

Total system protection: excellent heat transfer and dispersion. Anti-corrosion properties: outstanding corrosion protection. Antifreeze properties: superior cold temperature performance.

### **SPECIFICATIONS**

ASTM	D3306	MAZDA	C100CL005A4X
ASTM	D6210	MAZDA	C122CL005A4X
JIS	K2234:2018	MAZDA	FL 22
FORD	VC-10-A2	MITSUBISHI	DIA QUEEN SUPER LL COOLANT
FORD	WSS-M97B55	NISSAN	ANTI-FREEZE COOLANT (L250)
HONDA	08CLA010S0 Honda E Coolant	NISSAN	KE90299934
HONDA	TYPE 2	NISSAN	KE90299944
HYUNDAI	00232-19010	NISSAN	L255N
HYUNDAI	07100-00200	RENAULT	RX TYPE E COOLANT
HYUNDAI	07100-00400	SUBARU	Coolant 16218
HYUNDAI	Long Life Coolant	SUZUKI	(SUPER) LL COOLANT
LEXUS	SFU	TOYOTA	TSK 2601G-8A
MAZDA	000077508E20		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results	
рН	ASTM D1287		8.3	
Density at 20°C	ASTM D4052	g/ml	1.064	
Colour	VISUAL		DARK BLUE	
Freezing point (refracto)	ASTM D3321	°C	-36	
Water content	ASTM D1123	% wt/wt	50	

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### **CHAMPION CHEMICALS NV**

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 3 870 00 00 www.championlubes.com

