WOLF AROW ISO 22

02/03/2026
4004

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

FEATURES

Anti-wear and oxidation stability: superior protection
Anti-foam properties: excellent anti-foam properties
Temperature stability: adequate viscosity stability

SPECIFICATIONS

AFNOR	NF E 48-603 HM	JCMAS	HK P041
AFNOR	NF E 48-690	PARKER (DENISON)	HF-0, HF-1, HF-2
AFNOR	NF E 48-691	SAE	MS1004
AGMA	9005-E02-RO	SEB	181222
AIST	126 (US Steel)	VICKERS	I-286-S3
AIST	127 (US Steel)	DENISON	HF-2
ASTM	D6158 HL, HM	EATON VICKERS	I-286-S
DIN	51524 Part 2	EATON VICKERS	M-2950-S
ISO	11158, HM	EATON	E-FDGN-TB002-E
ISO	20763	EATON	M-2950-S (35VQ25 pump test)
ISO	6743-4, HM	GM	LS2 AW hyd.oil

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	21.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	4.4
Viscosity index	ASTM D2270		117
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	195

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV