

CHAMPION ANTIFREEZE EVO LL

High-performing coolant concentrate based on ethylene glycol with state-of-the-art PSi-OAT corrosion protection technology, for modern high performance engines. With the PSi-OAT technology, organic acids work together with mineral inhibitors for the best possible protection.

This G12 evo coolant concentrate can be used in G13, G12++, G12+, and G11 applications.

APPLICATIONS

This concentrate must be diluted with water before use. It may only be used in a concentration of at least 33 vol% to a maximum of 60 vol%. We recommend a mixing ratio of 50:50 [vol.%] with only demineralised or distilled water.

It offers long-term protection in VW TL 774 L [G12 evo] applications and many more OEM applications.

FEATURES

Total system protection: excellent heat transfer and dispersion.

Anti-corrosion properties: outstanding corrosion protection.

Antifreeze properties: superior cold temperature performance.

SPECIFICATIONS

AFNOR	NF R 15-601	ALFA ROMEO	SFU
ASTM	D1384	APRILIA	SFU
ASTM	D3306	ATLAS	SFU
ASTM	D4340	AUDI	SFU
ASTM	D4985	BMW	LC-18
ASTM	D6210	BMW	LC-87
AUSTRALIEN STD	AS 2108-2004	BMW	LC-97
BS	6580-2010	BUGATTI	SFU
CHINESE STANDARD	GB 29743	BYD	SFU
CUNA	NC 956-16	CASE	JIC-501
JIS	K2234:2018	CASE	MAT 3624
KOREAN STD	KS M 2142	CATERPILLAR	GCM34
MIL	BT-PS-606 A	CHEVROLET	SFU
MIL	DCSEA 615/C	CHRYSLER	SFU
MIL	E/L-1415b	CITROËN	-
MIL	FS 6850-0951	CLAAS	SFU
MIL	TL 6850-0038	CUMMINS	85T8-2
NATO	S759	CUMMINS	CES 14439
ÖNORM	V5123	CUMMINS	CES 14603
POLISH STANDARD	PN-C-40007	DACIA	SFU
SAE	J1034	DAEWOO	SFU
SAE	J1941	DAF	MAT 74002
SAE	J814	DAIHATSU	SFU
SANS	1251:2005	DEUTZ	DQC-CA-14
SWISS FED.LAB	EMPA 170'803	DEUTZ	DQC-CB-14
UNE	26-361-88/1	DEUTZ	DQC-CC-14
2G	SFU	DEUTZ-FAHR	SFU

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS

DODGE	SFU
DTFR	29C100
DTFR	29C110
DTFR	29C120
DUCATI	SFU
EICHER ENGINES	SFU
FAUN	SFU
FENDT	SFU
FERRARI	SFU
FIAT	SFU
FORD	ESD-M97B49-A
FORD	MU7J 19544 BA
FORD	SFU
FORD	WSS-M97B44-D
FORD	WSS-M97B57-A1
FUSO	SFU
FVV STD	FVV R 530:2005
GILERA	SFU
GM	B 040 1065
GM	GMW 3420
GMC	SFU
HINO	SFU
HITACHI	SFU
HONDA	SFU
HUERLIMANN	SFU
IRISBUS	SFU
IRIZAR	SFU
ISUZU	SFU
IVECO	18-1830
JAGUAR	CMR 8229
JAGUAR	E-VEHICLES
JAGUAR	SFU
JAGUAR-LAND ROVER	STJLR.651.5003
JD	SFU
JEEP	SFU
JENBACHER	TA 1000-0200
KAWASAKI	SFU
KOBELCO	SFU
KOMATSU	SFU
KTM	SFU
KYMCO	SFU
LADA	SFU
LAMBORGHINI	SFU
LAMBORGINI	-
LAND ROVER	E-VEHICLES
LAND ROVER	SFU
LAND ROVER	STJLR.651.5003
LEXUS	SFU
LIEBHERR	LH-00-COL5C
LIEBHERR	SFU
LOTUS	SFU
MAHLE	SFU
MAN	175D
MAN	324 NF
MAN	324 Si-OAT
MAN	324 Si-OAT EVO

MAN	324 SNF
MAZDA	SFU
MB	325.0
MB	325.3
MB	325.5
MB	325.6
MIL	FSD 8704
MINI	LC-87
MTU	MTL 5048
MWM	SFU
NISSAN	SFU
OPEL	B 040 240
OPEL	GME L1301
OPEL	SFU
PERKINS	SFU
PIAGGIO	SFU
PORSCHE	SFU
PSA	SFU
RENAULT	RTCS-2
RENAULT	SFU
ROLLS-ROYCE	LC-87
ROLLS-ROYCE	MTL 5048
ROLLS-ROYCE	SFU
ROVER/MG	SFU
SAAB	690 1599
SAAB	SFU
SAME	SFU
SCANIA	SFU
SCANIA	TB 1451
SEAT	SFU
SETRA	SFU
SKODA	SFU
SMART	SFU
STEYER MOTORS	SFU
SUBARU	SFU
SYM	SFU
TADANO	SFU
TESLA	SFU
TGB	SFU
TOYOTA	SFU
TRIUMPH	SFU
VAN HOOL	SFU
VAUXHALL	GME L1301
VAUXHALL	GMW 3420
VOLVO	TR-31854114-002
VOLVO	VCS-2
VW	TL 774-C [G11]
VW	TL 774-D [G12]
VW	TL 774-F [G12+]
VW	TL 774-G [G12++]
VW	TL 774-J [G13]
VW	TL 774-L [G12 EVO]
YAMAHA	SFU
YANMAR	SFU

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Freezing point 50% vol. AF	ASTM D1177	°C	-36
Reserve alkalinity	ASTM D1121	ml 0.1M HCl	10.5
Density at 20°C	ASTM D4052	g/ml	1.125
Colour	VISUAL		PINK

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

