

CHAMPION COMPETE

C2/C3 5W-30

This API SQ engine oil is designed to meet the core requirements of ACEA and API for passenger cars. It offers complete protection of both the aftertreatment system and the engine, regardless the driving conditions. This lubricant may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Formulated to meet recent OEM specifications. It can be used to service a wide range of EURO 4 and EURO 5-engines of different manufacturers, with or without diesel particulate filter.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Fuel economy: lower fuel consumption and CO₂ emissions.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

| | | | |
|-------------|-------------|-----------|--------|
| ACEA | C2 | MB | 229.31 |
| ACEA | C3 | MB | 229.51 |
| API | SQ | MB | 229.52 |
| BMW | LONGLIFE-04 | VW | 505 00 |
| GM | dexos™2 | VW | 505 01 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.854 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 74.2 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 12.3 |
| Viscosity index | ASTM D2270 | | 164 |
| Pour point | ASTM D6892 | °C | -39 |
| Flash Point COC | ASTM D92 | °C | 220 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

