

WOLF OFFICIALTECH 10W-30 UHPD MF

25/09/2026
15765

This oil for gas powered HD engines offers exceptional wear resistance. It is capable of maintaining its original composition thanks to its outstanding oxidation resistance, shear resistance and aeration control, giving it an increased drain interval compared to previous formulations.

APPLICATIONS

Both modern and older gas powered engines benefit from this heavy-duty engine oil for most OEMs, making it a perfect match for a wide range of engine types. It is capable of offering optimal protection to a range of Caterpillar, Mack, Renault, Volvo and other market-leading engines with or without after-treatment system, turbo- or supercharger. It is compatible with emission control technology EURO IV, V and VI for trucks; as well as stage IIIB, IV, V and Tier 4i, 4f for heavy-duty off-road.

FEATURES

Engine cleanliness: consistent operating hours
High wear protection: durable engine lifespan
Oxidative stability: great oil performance

SPECIFICATIONS

ACEA	E11	DAF	PSQL 2.1 E
ACEA	E6-16	DAF	PSQL 2.1 E LD
ACEA	E7	DAF	PSQL 2.4
ACEA	E8	DAF	PSQL 2.4 LD
ACEA	E9-16	DETROIT DIESEL	DFS 93K215
API	CI-4	DETROIT DIESEL	DFS 93K218
API	CI-4 Plus	DETROIT DIESEL	DFS 93K222
API	CJ-4	DEUTZ	DQC IV-10 LA
API	CK-4	DEUTZ	DQC-III-10 LA
API	SN	DEUTZ	DQC-III-18 LA
JASO	DH-1	DEUTZ	DQC-IV-18 LA
JASO	DH-2	DTFR	13D110
ALLISON	C4	DTFR	15B110
CATERPILLAR	ECF-1a	DTFR	15C100
CATERPILLAR	ECF-2	DTFR	15E100
CATERPILLAR	ECF-3	DTFR	approval 15C110
CATERPILLAR	TO-2	DTFR	approval 15C120
CUMMINS	CES 20076	FORD	WSS-M2C171-F1
CUMMINS	CES 20077	IVECO	18-1804 Classe T2 E7
CUMMINS	CES 20078	IVECO	18-1804 Classe TLS E9
CUMMINS	CES 20081	JD	JDQ-78X
CUMMINS	CES 20085	LIEBHERR	LH-00-ENG5C LA
CUMMINS	CES 20086	MACK	approval EO-S 4.5
CUMMINS	CES 20092	MACK	EO-M PLUS
CUMMINS	CES 20100	MACK	EO-N
DAF	EXTENDED DRAIN	MACK	EO-N Premium Plus

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



MACK	EO-O Premium Plus	RENAULT	RLD
MAN	M3271-1	RENAULT	RLD-2
MAN	M3477	RENAULT	RLD-4
MAN	M3575	RENAULT	RXD
MAN	M3775	SCANIA	LA
MB	235.28	VOITH	Retarder Oil Class B
MTU	Oil Category 2.1	VOLVO	approval VDS-4.5
MTU	Oil Category 3.1	VOLVO	VDS-3
RENAULT	approval RLD-3	VOLVO	VDS-4
RENAULT	RGD		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm²/s	76.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.0
Viscosity index	ASTM D2270		153
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

