

# WOLF GUARDTECH 15W40 SL/CF

14/04/2025  
14136

This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4-08. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

## APPLICATIONS

4-stroke gasoline passenger cars engines (multi-valve, turbo, etc.); 4-stroke diesel engines, with or without turbo. High compatibility with biodiesel, based on extensive field trials.

## FEATURES

Total engine protection: engine protection and cleanliness

## SPECIFICATIONS

ACEA	A3/B3	MB	229.1
ACEA	A3/B4	PSA	B71 2295
API	SL/CF	VW	501 01 Level
FIAT	9.55535-D2	VW	505 00 Level
FIAT	9.55535-G2		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	103
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.7
Viscosity index	ASTM D2270		130
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-33
CCS viscosity at -20°C	ASTM D5293	mPa.s	6800
Sulfated Ash	ASTM D874	Mass %	1.03
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

