

# WOLF ESSENTIAL

## CI-4/SL 15W40

14/04/2025  
75702

This engine oil meets the prime requirements of ACEA and API for heavy-duty engines. It combines wear reducing- and cleaning properties into one lubricant.

### APPLICATIONS

Suitable for all modern Euro II, III and some Euro IV diesel engines of heavy-duty equipment, making it a great lubricant for mixed fleet maintenance.

### FEATURES

Engine protection: outstanding engine cleanliness and durability

### SPECIFICATIONS

|      |                  |     |       |
|------|------------------|-----|-------|
| ACEA | A3/B4            | API | CG-4  |
| ACEA | E7               | API | CH-4  |
| API  | approval CI-4/SL | MB  | 229.1 |

### TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit     | Average results |
|------------------------------|------------|----------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml     | 0.882           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm²/s    | 95.7            |
| Kinematic viscosity at 100°C | ASTM D445  | mm²/s    | 13.7            |
| Viscosity index              | ASTM D2270 |          | 145             |
| B.N. (HClO4 method)          | ASTM D2896 | mg KOH/g | 8               |
| Pour point                   | ASTM D6892 | °C       | -33             |
| Flash Point COC              | ASTM D92   | °C       | 225             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

