

# WOLF ELECTRUM MULTI E-ATF FLUID

14/04/2025  
65305

This is a new generation E-motor and transmission fluid for use with battery electric vehicles (BEV).

## APPLICATIONS

Specifically designed for transmission applications in wet motor battery electric vehicles (BEV).

## FEATURES

Optimum electrical properties: allowing high voltages applications.

Excellent wear and gear protection: even at ultra-low viscosity.

Outstanding material compatibility: even with newer materials.

## SPECIFICATIONS

TESLA	EDF-2 (1616951-04-A)	VW	G 053 013
TESLA	KAF 1 (1646886-04-A)		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.837
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	16.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	3.92
Viscosity index	ASTM D2270		140
Pour point	ASTM D6892	°C	-57
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	3800
Copper corrosion (150°C, 3h)	ASTM D130		1a
FZG (A10/16.6R/90)	CEC L-84-02 / ISO 14635-2		9.9
Cu Rating / Diss (150C, 168h)	ASTM D130 / ISO2160	./ppm	4a/57
Volume Resistivity at 80C	ASTM D1169	MOhm.m	42
DKA Oxidation at 170C, 192h (Delta KV100)	CEC L-48-00	%	1.7

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

