

WOLF MOTO & SCOOTER 2T

21/05/2026
1931

This semi-synthetic two-stroke scooter engine oil with an advanced additive package guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of scooter enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for the engines of 2-stroke scooters. Please follow the dosage recommendations of the equipment manufacturer.

FEATURES

Extended scooter lifespan thanks to the oil's protective properties.: Extended scooter lifespan thanks to the oil's protective properties.

Protects the original riding comfort.: Protects the original riding comfort.

Simpler fluid management thanks to the oil's broad applicability.: Simpler fluid management thanks to the oil's broad applicability.

SPECIFICATIONS

API	TC	JASO	FC
ISO	L-EGB	JASO	FD
ISO	L-EGD		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	76.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.4
Viscosity index	ASTM D2270		120
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	1.7
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

