

WOLF ELECTRUM LC COOLANT FCEV

14/04/2025
65342

This low electrical conductivity fuel cell coolant is a mixture of ultra-pure water and high-purity antifreeze grade glycol.

It contains non-ionic additives for corrosion protection and electrical conductivity control.

APPLICATIONS

Specifically designed as a low electrical conductivity coolant for direct cooling of fuel cell stacks.

FEATURES

Electrical safety: low and stable electrical conductivity ($< 5 \mu\text{S}/\text{cm}$).

Material protection: corrosion protection for fuel cell system components.

Compatibility: compatible with fuel cell cooling system components.

SPECIFICATIONS

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 20°C	ASTM D4052	g/ml	1.065
Colour	VISUAL		TRANSPARENT
Freezing point	ASTM D1177	°C	-35
ELECTRIC CONDUCTIVITY (25°C)	ASTM D1125	$\mu\text{S}/\text{cm}$	< 2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

