

CHAMPION OEM SPECIFIC 5W40 C3

This synthetic engine oil is developed to suit the needs of some of the highest performing petrol engines. Thanks to its highly durable formula, this lubricant offers improved fuel economy and complete engine protection within even the most demanding engine designs. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This engine oil enhances the performance of several W12, V10 and V8 engines of several manufacturers. Its top quality properties are proven by the VW 511 00 and Porsche C40 specifications, which broadens the lubricant's applicability to a range of Audi, Bentley and Lamborghini cars.

FEATURES

Fuel economy: low fuel consumption and CO2 emissions

Aftertreatment protection: full aftertreatment device protection

Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

ACEA	C3	MB	226.5
API	approval SN	MB	229.31
API	CF	MB	229.51
ALFA ROMEO	SFU	MB	229.52
BMW	LOGLIFE-04	MINI	SFU
BYD	SFU	MITSUBISHI	SFU
CADILLAC	SFU	MORGAN	SFU
CHEVROLET	SFU	OPEL	OV 040 1547 - D40
CHRYSLER	SFU	OPEL	SFU
DACIA	SFU	PIAGGIO	SFU
DODGE	SFU	PORSCHE	approval C40
FERRARI	SFU	RENAULT	RN 0700
FIAT	9.55535-GH2	RENAULT	RN 0710
FIAT	9.55535-S2	ROLLS-ROYCE	SFU
FORD	WSS-M2C917-A	SAAB	SFU
FREIGHTLINER	SFU	SAMSUNG	SFU
GAZ	SFU	SEAT	SFU
GM	dexos2™	SKODA	SFU
GREAT WALL	SFU	SMART	SFU
HONDA	SFU	SSANG YONG	SFU
HYUNDAI	SFU	SUZUKI	SFU
INFINITI	SFU	TOYOTA	SFU
ISUZU	SFU	VW	505 00
KIA	SFU	VW	505 01
LADA	SFU	VW	approval 511 00
LANCIA	SFU		
LANDWIND	SFU		
LIFAN	SFU		
MASERATI	SFU		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	73.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.5
Viscosity index	ASTM D2270		191
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

