

# REGULAR SAE 30 API SA

*This is a pure, mineral engine oil, made of natural, paraffinic, highly refined base oils. It contains an antifoam additive. It is characterized by a good natural resistance to oxidation, low levels of carbon residue and a high natural viscosity index.*

## APPLICATIONS

This oil can be used as a non-detergent motor oil, e.g. for very old vehicles that do not allow detergent motor oils. Lubrication of air compressors with a low end temperature or when an oil DIN VC-classification is required. The equivalent ISO viscosity grade is 100.

## FEATURES

Total engine protection: engine protection and cleanliness

## SPECIFICATIONS

API

SA

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.883
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	100
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.2
Viscosity index	ASTM D2270		97
Pour point	ASTM D6892	°C	-24
Flash Point COC	ASTM D92	°C	252

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION