

# CHAMPION LIFE EXTENSION ATF DII

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

## APPLICATIONS

It can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

## FEATURES

Anti-wear protection: extended transmission life  
Extended oil life: optimized thermal and oxidation stability

## SPECIFICATIONS

<b>ALLISON</b>	C4	<b>MB</b>	236.7
<b>CATERPILLAR</b>	T0-2	<b>VOITH</b>	H55.6335xx
<b>DTFR</b>	13C140	<b>ZF</b>	TE-ML 03D
<b>FIAT</b>	9.55550-AG1	<b>ZF</b>	TE-ML 04D
<b>FORD</b>	M2C-138CJ, Mercon	<b>ZF</b>	TE-ML 09
<b>GM</b>	6137-M DEXRON II-D	<b>ZF</b>	TE-ML 11A
<b>MAN</b>	339 V1/Z1	<b>ZF</b>	TE-ML 14A
<b>MB</b>	236.5	<b>ZF</b>	TE-ML 17C

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	37
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.4
Viscosity index	ASTM D2270		170
B.N. [HClO <sub>4</sub> method]	ASTM D2896	mg KOH/g	3
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

