

MULTIGRADE LONGLIFE III C3 5W-30

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is specifically formulated to meet the most demanding VW specifications available today - VW 504.00 and 507.00. It is a Mid SAPS oil which meets Euro 4, 5 and 6 norms and provides protection to the Diesel Particulate Filter. THIS PRODUCT REPLACES LONGLIFE III 5W30

APPLICATIONS

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications. For almost any vehicle in the VAG Group with extended oil drain intervals (30.000 km or 2 years). It is particularly designed for downsized Turbocharged Gasoline Direct Injection (TGDl) engines to mitigate LSPI (Low Speed Pre Ignition).

FEATURES

- Aftertreatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: lower fuel consumption and CO2 emissions.

PERFORMANCE PROFILE

SPECIFICATIONS

ACEA - C2	BMW - LONGLIFE-04	MB - 229.51	OPEL - OV 040 1547 - G30
ACEA - C3	FIAT - 9.55535-S3	MB - 229.52	PORSCHE - C30
API - SN Plus	GM - dexos™1 Gen 2	OPEL - GM-LL-A-025	VW - 503 01
API - SP	GM - dexos™2	OPEL - GM-LL-B-025	VW - 504 00/507 00
API - SQ	MB - 229.31	OPEL - OV 040 1547 - D30	

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	64.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.6
Viscosity index	ASTM D2270		177
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.9
Pour point	ASTM D6892	°C	-42
CCS viscosity at -30°C	ASTM D5293	mPa.s	5600
Sulfated Ash	ASTM D874	Mass %	0.78
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.