

WOLF ECOTECH CVT-ATF FLUID

13/12/2025
3029

This is a multifunctional full synthetic lubricant that has been designed for both CVT and step automatic transmissions. The multi-vehicle suitability of this oil enables optimized supply chain, reduced operational cost and mitigated misapplication risk.

It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

It is suitable for continuously variable transmissions (using steel push-belts or chains) and for the latest generation of high efficiency step automatic transmissions where the manufacturer recommends the specifications as referred to in the extensive list on this technical data sheet.

FEATURES

Anti-wear protection: significantly extended transmission life.

Extended oil life: excellent thermal and oxidation stability.

Frictional properties: very smooth gear shifting, no vibration.

SPECIFICATIONS

ACURA	ATF-Z1	CHRYSLER	Dodge/Jeep/ 68043742AA
AIISIN-WARNER	AW-1	DAEWOO	LT 71141
AIISIN-WARNER	AW-2	DAIHATSU	AMIX CVTF DFC
AIISIN-WARNER	JWS 3309(T-IV)	DAIHATSU	AMIX CVTF DFE
AIISIN-WARNER	JWS 3324(W5)	DAIHATSU	AMIX CVTF DTC
ALLISON	C3	DAIHATSU	AMIX CVTF-DC
ALLISON	C4	DAIHATSU	AMMIX ATF D II
AUDI	TL 52180	DAIHATSU	AMMIX ATF D III SP
BMW	83 22 0 136 376	DAIHATSU	FLUID TC
BMW	83 22 2 344 206	DODGE	NS-2/CVTF+4
BMW	83 22 2 344 207	DTFR	13C140
BMW	83 22 9 407 765	DTFR	13C150
BMW	ATF 4	DTFR	13C170
BMW	ATF 5	FIAT	T-IV type
BMW	ATF 6	FORD	CVT23
BMW	ETL 7045E	FORD	CVT30
BMW	ETL 8072B	FORD	ESP-M2C166-H
BMW	EZL799/EZL799A	FORD	FRN 5
BMW	JWS 3309(T-IV)	FORD	MERCON
BMW	LA 2634	FORD	MERCON C
BMW	LT 71141	FORD	MERCON SP
BMW	ZF 5HP18FL,5HP24,5HP30	FORD	WSS-M2C922-A1
BOSCH REXROTH	TE-ML 09	FORD	WSS-M2C924-A
CATERPILLAR	TO-2	FORD	WSS-M2C928-A
CHRYSLER	ATF +, +2, +3	FORD	WSS-M2C933-A
CHRYSLER	Dodge MOPAR AS 68 RC (T-IV) ,	FORD	XT-2 QSM (Syn)
	JWS 3309	FORD	XT-2QDX (M)

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



FORD	XT-6-QSP	MAZDA	ATF 3317
FUJIIYUUKO	i-CVTF FG	MAZDA	ATF A7
FUSO	ATF -SP III	MAZDA	ATF D-II
FUSO	ATF-A4	MAZDA	ATF F-1
FUSO	ATF-II	MAZDA	ATF FZ
GEELY	CVTF-EX1	MAZDA	ATF M-III
GM	1940700	MAZDA	ATF M-V (Type M5)
GM	1940767	MAZDA	ATF N-1
GM	21005966	MAZDA	ATF S-1
GM	22717466	MAZDA	CVTF 3320
GM	88863400	MB	236.20/CVT28
GM	88863401	MB	236.6
GM	88900925	MINI	EZL799/EZL799A/CVT V1
GM	93160393	MINI	T-IV
GM	9985010	MITSUBISHI	CVTF ECO J4
GM	9985835	MITSUBISHI	CVTF J-1
GM	9986195	MITSUBISHI	CVTF J-4
GM	AW-1	MITSUBISHI	CVTF J-4+
GM	CVTF GREEN 2/SATURN DEX-CVT	MITSUBISHI	Diaqueen ATF-PA
GM	DEXRON II	MITSUBISHI	Diaqueen AW
GM	DEXRON II-D	MITSUBISHI	Diaqueen J2
GM	DEXRON II-E	MITSUBISHI	Diaqueen J3
GM	DEXRON III-G	MITSUBISHI	Diaqueen SK
GM	DEXRON III-H	MITSUBISHI	Diaqueen SP
GM	DEXRON TYPE A, SUFFIX A	MITSUBISHI	Diaqueen SP-II
GM	HP CVTF 95529854	MITSUBISHI	Diaqueen SP-III
HINO	Blue Ribon ATF	MITSUBISHI	Diaqueen SP-IV
HONDA	ATF Z-1	NISSAN	MATIC-C
HONDA	DW-1	NISSAN	MATIC-D
HONDA	HCF-2/HMMF (No Start Clutch)	NISSAN	MATIC-J
HONDA	Type 3.0 and 3.1	NISSAN	MATIC-K
HONDA	Ultra HEVF-Type 1	NISSAN	MATIC-S
HYUNDAI	040000C90SG	NISSAN	NS-1/NS-2/NS-3/Matic W
HYUNDAI	Dex-II/SP-II	PORSCHE	000.043.205.09
HYUNDAI	SP-CVT1	PORSCHE	000.043.205.28
HYUNDAI	SP-II M	PORSCHE	999.917.547.00(A2)
HYUNDAI	SP-III	PORSCHE	LA 3403-M115
HYUNDAI	SP-IV M	PORSCHE	T-IV (JWS 3309)
HYUNDAI	SP-IV M1	PORSCHE	Z 000169756
ISUZU	08200-9001	PSA	1635056080
ISUZU	BESCO ATF-II	PSA	9730 AE
ISUZU	BESCO ATF-III	PSA	B71 2340
ISUZU	BESCO ATF-SP	PSA	P/N Z 000169756
ISUZU	SCS Fluid	PSA	ZF 4HP20
JAGUAR	ATF 3403 JLM 20238	PUNCH	EZL799/EZL799A
JAGUAR	ATF 3403 M115	RENAULT	CVT CK/SK/FK
JAGUAR	JLM 20292	RENAULT	DPO/AL4
JAGUAR	LT71141 ZF 5HP24	RENAULT	ELFMATIC
JASO	M315-2013 1A	RENAULT	MATIC-D2
JASO	M315-2013 1A-LV	RENAULT	Samsung SATF-D
JASO	M315-2013 2A	SAAB	93 160 393
JEEP	ATF +3	SAAB	93 165 147
JEEP	NS-2/CVTF+4	SAAB	T-IV (JWS 3309)
KIA	SP-CVT 1	SCION	(all Vehicles)
LEXUS	JWS 3309	SSANG YONG	DSIH 5M-66

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



SUBARU	ATF	TOYOTA	TYPE T-III
SUBARU	ATF 5AT	TOYOTA	TYPE T-IV
SUBARU	ATF, ATF HP	VOLVO	1161521
SUBARU	DEXRON-II	VOLVO	1161540/1161640
SUBARU	e-CVTF	VOLVO	97325
SUBARU	High Torque CVTF	VOLVO	97335
SUBARU	i-CVTF	VOLVO	CE 97340
SUBARU	i-CVTF FG	VOLVO	CE 97341
SUBARU	K0140Y0700	VOLVO	CVT 4959
SUBARU	Lineartronic CV-30	VW	5HP (18FL, 30)
SUBARU	Lineartronic CVTF II	VW	5HP (19FL, 24A)
SUZUKI	AT OIL 5D06	VW	5HP (ZF 5 HP 30)
SUZUKI	ATF 2326	VW	G 052 025
SUZUKI	ATF 2384K	VW	G 052 055
SUZUKI	ATF 3314	VW	G 052 162
SUZUKI	ATF 3317	VW	G 052 180
SUZUKI	ATF AW-1	VW	G 052 516
SUZUKI	ATF JWS 3309	VW	G 052 990
SUZUKI	CVTF 3320	VW	G 053 001
SUZUKI	CVTF 4401	VW	G 053 025
SUZUKI	CVTF GREEN 2	VW	G 053 162 A1
SUZUKI	NS-2/SHELL GREEN 1 V	VW	G 055 025
TOYOTA	ATF D-II	VW	G 055 540
TOYOTA	ATF D-III	VW	TL 52540-A
TOYOTA	ATF WS	ZF	TE-ML 05L
TOYOTA	CVT FE	ZF	TE-ML 09X
TOYOTA	TC	ZF	TE-ML 21L
TOYOTA	TYPE T		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	15000
Flash Point COC	ASTM D92	°C	190
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.