

# CHAMPION ACTIVE DEFENCE

## SAE 30 CF-4/SG

Universal mineral oil of high quality, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines operating in cold climatic conditions.

### APPLICATIONS

This oil is particularly recommended for fixed diesel engines, material for public works and mixed fleets of trucks and cars.

### FEATURES

Total engine protection: performance in keeping the engine clean

### SPECIFICATIONS

<b>ACEA</b>	E2/E1	<b>MB</b>	227.0
<b>API</b>	CF-4/SG	<b>MTU</b>	Oil Category 1
<b>MIL</b>	L-2104 E	<b>ZF</b>	TE-ML 03A
<b>MIL</b>	L-46152 E	<b>ZF</b>	TE-ML 04A
<b>ALLISON</b>	C4	<b>ZF</b>	TE-ML 04B
<b>CATERPILLAR</b>	T0-2	<b>ZF</b>	TE-ML 07D
<b>MAN</b>	270		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm²/s	103
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.8
Viscosity index	ASTM D2270		103
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	10.9
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.88
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

