

# WOLF ELECTRUM LC COOLANT

14/04/2025  
65341

This is a dedicated coolant for battery thermal management of Battery Electric Vehicles (BEV). Based on proven OAT technology, it combines all-round corrosion protection with reduced electrical conductivity to enhance electrical safety. It is specifically designed as a reduced electrical conductivity coolant (<100µS/cm) for indirect cooling in the battery cooling loop of Battery Electric Vehicles.

## APPLICATIONS

Designed as a liquid heat transfer medium for indirect cooling of battery cells, modules and packs where coolants with low conductivity (LC) are required.

It is not intended for use in traditional engine coolant applications.

It should not be applied in fuel cell nor immersive cooling applications where direct electrical contact is possible.

## FEATURES

Electrical safety: reduced electrical conductivity.

Material protection: ensured longevity of components and reduced maintenance.

Sustainability: carefully selected organic additive technology.

## SPECIFICATIONS

HYUNDAI 00232-19091/07100J2A20EU KIA 07100J2A20EU/UM020-CH237

## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit  | Average results |
|------------------------------|------------|-------|-----------------|
| Density at 20°C              | ASTM D4052 | g/ml  | 1.066           |
| Colour                       | VISUAL     |       | LIGHT BLUE      |
| Freezing point               | ASTM D1177 | °C    | -37             |
| ELECTRIC CONDUCTIVITY (25°C) | ASTM D1125 | µS/cm | 96              |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

