

WOLF OE LEVELTECH OW-30 LL III

24/02/2026
75617

This engine oil is formulated to meet the specifications of different OEMs. It reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protecting, regardless the driving conditions.

APPLICATIONS

Its formulation is designed to meet the VW 504.00 and 507.00 specifications. This engine oil can be used to service a range of different EURO 4 and EURO 5-engines equipped with diesel particulate filters.

FEATURES

Aftertreatment protection: full aftertreatment device protection.
Fuel economy: lower fuel consumption and CO₂ emissions.
Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C2	FIAT	9.55535-S3
ACEA	C3	MB	229.31
API	SN Plus	MB	229.51
API	SP	MB	229.52
API	SQ	PORSCHE	C30
BMW	LOGLIFE-04	VW	504 00/507 00
FIAT	9.55535-DS1	VW	TL 525 45
FIAT	9.55535-GS1		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	66,6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12,1
Viscosity index	ASTM D2270		181
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,3
Pour point	ASTM D6892	°C	-39

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

