

# WOLF SUPER CPO 10W40

05/06/2026  
1726

This is a semi synthetic lubricant based on carefully selected highly refined base oils for use in public works. It meets the specifications of most manufacturers, both in terms of engine and gear oils. Its high viscosity index allows the use in all weather conditions.

## APPLICATIONS

Diesel engines with or without turbo and 4-stroke gasoline engines. Without limitation recommended for all uses in the area of off-road equipment : motors, mechanical transmissions, transaxles, hydraulic systems, wet brakes and compressors, pumps and reductions.

## FEATURES

Total engine protection: outstanding engine cleanliness and durability

## SPECIFICATIONS

ACEA	E3	NH	NH 410B
AFNOR	NF E 68-603 E	NH	NH 420A
API	CG-4	Sauer Sunstrand/Danfoss	Hydro Static Trans Fluid
API	GL-4	ZF	TE-ML 03A
API	GL-5 (Low speed/high torque)	ZF	TE-ML 05K
API	SF/CE	ZF	TE-ML 06A
DIN	51524 T3 HVLPD	ZF	TE-ML 06B
MIL	L-2104 D	ZF	TE-ML 06C
MIL	L-46152 B	ZF	TE-ML 07B
ALLISON	C4 (Agriculture applic.)	ZF	TE-ML 07D
CASE	MAT 3525		
CASE	MAT 3526		
CATERPILLAR	TO-2		
EATON VICKERS	I-280-S		
EATON VICKERS	M-2950-S		
FORD	ESN-M2C134 C/D		
FORD	ESN-M2C159 B/C		
FORD	FNH 82009203		
JD	J20C		
JD	J27		
MAN	271		
MB	227.1		
MF	M 1135		
MF	M 1139		
MF	M 1143		
MF	M 1144		
MF	M 1145		
NH	NH 024C		

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)



## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.868
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	88.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.8
Viscosity index	ASTM D2270		160
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	11.1
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6550
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

