

WOLF GUARDTECH 10W40 B4 DIESEL

21/05/2025
23126

This is a semi synthetic lubricant based on carefully selected highly refined base oils. It is designed for the lubrication of four-stroke diesel cars, including diesel engines with direct injection such as Common Rail, HDI, CDI, etc. The use of high-quality components ensures that the oil has a great fluidity at low temperature and a stable viscosity at high temperatures. Its low ash formulation is combined with a high resistance to ageing.

APPLICATIONS

This oil is used for most diesel engines, both normally aspirated and supercharged. It is particularly recommended for direct-injection diesel engines. Because of its excellent viscosity index it can be used all year round.

FEATURES

Total engine protection: performance in keeping the engine clean
Cold start: very good fluidity at low temperature

SPECIFICATIONS

ACEA	A3/B3-16	MB	229.1
ACEA	A3/B4	VW	501 01
API	SL/CF	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm²/s	91
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.7
Viscosity index	ASTM D2270		153
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

