

# WOLF AGRIFLOW 4T 10W30

14/04/2025  
13125

This is a low viscosity engine oil for gasoline and diesel engines. It combines good fluidity at low temperature with low ash content, while maintaining excellent detergent and dispersant properties.

## APPLICATIONS

Used for the lubrication of light gasoline and diesel engines, which prefer this viscosity class. Particularly suitable for 4T- auxilliary engines and horticulture material (e.g. Honda).

## FEATURES

Total engine protection: good engine protection and cleanliness  
Temperature stability: adequate viscosity stability

## SPECIFICATIONS

ACEA	A2	API	SJ/CF
ACEA	B2	JASO	MA

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm²/s	71.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.1
Viscosity index	ASTM D2270		146
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.3
Pour point	ASTM D6892	°C	-33
CCS viscosity at -25°C	ASTM D5293	mPa.s	6500
Sulfated Ash	ASTM D874	Mass %	0.7
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.