

CHAMPION LIFE EXTENSION

85W140 GL 5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties: easy gear shifting

Anti-wear protection: long transmission life

SPECIFICATIONS

API	GL-4	ZF	TE-ML 07A
API	GL-5	ZF	TE-ML 12E
API	MT-1	ZF	TE-ML 16B
MIL	L-2105 C	ZF	TE-ML 16C
MIL	L-2105 D	ZF	TE-ML 16D
MIL	L-2105 E	ZF	TE-ML 17B
MACK	GO-J	ZF	TE-ML 19B
SCANIA	STO 1:0	ZF	TE-ML 21A
ZF	TE-ML 05A		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.908
Kinematic viscosity at 40°C	ASTM D445	mm²/s	367
Kinematic viscosity at 100°C	ASTM D445	mm²/s	26.1
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-15
Copper corrosion [150°C, 3h]	ASTM D130		1B
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

