

CHAMPION NEW ENERGY ATF DIII

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

FEATURES

Frictional properties: smooth shift performance

Anti-wear protection: extended transmission life

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

ALLISON	C4
DTFR	13C140
DTFR	13C150
DTFR	13C170
FORD	MERCON
GM	6417-M DEXRON III-G
GM	DEXRON II-D
GM	DEXRON III-H
MAN	339 V1/Z1
MB	236.5
MB	236.6
MB	236.93
PSA	9730 AC
VOITH	H55.6335xx
VOLVO	STD 1273,25 [97325]
VOLVO	STD 1273,35 [97335]
VOLVO	STD 1273,37 [97337]
VOLVO	STD 1273,40 [97340]
VOLVO	STD 1273,41 [97341]
ZF	TE-ML 03D
ZF	TE-ML 04D
ZF	TE-ML 05L
ZF	TE-ML 09
ZF	TE-ML 11B
ZF	TE-ML 14A
ZF	TE-ML 17C
ZF	TE-ML 21L

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	33.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.1
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	17500
Flash Point COC	ASTM D92	°C	196
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

