

CHAMPION OEM SPECIFIC 5W30 C3 SP EXTRA

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

APPLICATIONS

This dexos 2™ is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2™ specification is backward compatible to older GM/Opel specifications [GM-LL-A-025 and GM-B-LL-025]. The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2™ lubricants. Broad application field with both ACEA C3/C2 and also covering API SP.

FEATURES

Total engine protection: outstanding engine cleanliness and durability.

Fuel economy: lower fuel consumption and CO₂ emissions.

Aftertreatment protection: full aftertreatment device protection.

SPECIFICATIONS

ACEA	C2	VW	505 00
ACEA	C3	VW	505 01
API	approval SN Plus		
API	approval SP		
BMW	approval LONGLIFE-04		
CHRYSLER	MS 11106		
FIAT	9.55535-S1		
FIAT	9.55535-S3		
FORD	WSS-M2C917-A		
GM	dexos™1 Gen 2		
GM	dexos™2		
HYUNDAI	SFU		
IVECO	18-1811 Classe SC1		
KIA	SFU		
MB	226.52		
MB	approval 229.31		
MB	approval 229.51		
MB	approval 229.52		
OPEL	approval OV 040 1547 - D30		
OPEL	approval OV 040 1547 - G30		
OPEL	GM-LL-A-025		
OPEL	GM-LL-B-025		
PSA	B71 2290-2014		
RENAULT	RN 0700		
RENAULT	RN 0710		
RENAULT	RN17 Level		
VW	502 00 < 2017		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.1
Viscosity index	ASTM D2270		175
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.5
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

