

WOLF OFFICIALTECH ATF D VI

14/04/2025
3008

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

APPLICATIONS

This high quality ATF can be used in automatic transmissions with torque converters of passenger cars, as well as in wet clutches and power steering units.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

GM	DEXRON VI	VOITH	H55.6335xx
MB	236.41		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.2
Viscosity index	ASTM D2270		154
Pour point	ASTM D6892	°C	- 45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

