

ATF DEXRON II

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

APPLICATIONS

It can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

FEATURES

- Anti-wear protection: extended transmission life
- Extended oil life: optimized thermal and oxidation stability

PERFORMANCE PROFILE

SPECIFICATIONS

ALLISON - C4	GM - 6137-M DEXRON II-D	VOITH - H55.6335xx	ZF - TE-ML 11A
CATERPILLAR - TO-2	MAN - 339 V1/Z1	ZF - TE-ML 03D	ZF - TE-ML 14A
DTFR - 13C140	MB - 236.5	ZF - TE-ML 04D	ZF - TE-ML 17C
FIAT - 9.55550-AG1	MB - 236.7	ZF - TE-ML 09	

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	37
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.4
Viscosity index	ASTM D2270		170
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	3
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.