

HYDRAULIC ISO 22

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

FEATURES

- Anti-wear and oxidation stability: superior protection
- Anti-foam properties: excellent anti-foam properties
- Temperature stability: adequate viscosity stability

PERFORMANCE PROFILE

SPECIFICATIONS

AFNOR - NF E 48-603 HM	AIST - 127 (US Steel)	SEB - 181222	test)
AFNOR - NF E 48-690	DIN - 51524 Part 2	VICKERS - I-286-S3	EATON VICKERS - I-286-S
AFNOR - NF E 48-691	ISO - 20763	DENISON - HF-2	EATON VICKERS - M-2950-S
AGMA - 9005-E02-RO	JCMAS - HK P041	EATON - E-FDGN-TB002-E	GM - LS2 AW hyd.oil
AIST - 126 (US Steel)	SAE - MS1004	EATON - M-2950-S (35VQ25 pump	

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	21.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	4.4
Viscosity index	ASTM D2270		117
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	195

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.