

# CHAMPION OEM LEVEL 0W-30 LL III

This engine oil is formulated to meet the specifications of different OEMs. It reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protecting, regardless the driving conditions.

## APPLICATIONS

Its formulation is designed to meet the VW 504.00 and 507.00 specifications. This engine oil can be used to service a range of different EURO 4 and EURO 5-engines equipped with diesel particulate filters.

## FEATURES

*Aftertreatment protection: full aftertreatment device protection.*

*Fuel economy: lower fuel consumption and CO<sub>2</sub> emissions.*

*Total engine protection: outstanding engine cleanliness and durability.*

## SPECIFICATIONS

<b>ACEA</b>	C2	<b>FIAT</b>	9.55535-S3
<b>ACEA</b>	C3	<b>MB</b>	229.31
<b>API</b>	SN Plus	<b>MB</b>	229.51
<b>API</b>	SP	<b>MB</b>	229.52
<b>API</b>	SQ	<b>PORSCHE</b>	C30
<b>BMW</b>	LONGLIFE-04	<b>VW</b>	504 00/507 00
<b>FIAT</b>	9.55535-DS1	<b>VW</b>	TL 525 45
<b>FIAT</b>	9.55535-GS1		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	66,6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.1
Viscosity index	ASTM D2270		181
B.N. [HClO <sub>4</sub> method]	ASTM D2896	mg KOH/g	9,3
Pour point	ASTM D6892	°C	-39

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

