25/09/2026 / 5097

CHAMPION CENTRAL HYDRAULIC FLUID ASIAN

This central hydraulic fluid is based on carefully selected very high quality base oils and the latest additive technology for the optimum functioning of hydraulic systems.
It is reliable power transmission fluid, even under difficult conditions, with a high and stable viscosity index

APPLICATIONS

This CHF is especially developed for the performance requirements of hydraulic systems (power steering) of Asian manufacturers in a wide temperature range.
Compatible with many common elastomers an sealing materials.

FEATURES

Pour point: great low temperature properties

SPECIFICATIONS

ACURA	08206-9002A	**MITSUBISHI**	DIAMOND SP III
HONDA	08206-9002A	**MITSUBISHI**	PS FLUID
HONDA	PSF-2	**NISSAN**	PSF-II
HONDA	PSF-S	**PSA**	9735 EJ
HONDA	PSF-V	**SUBARU**	K0209A0080
HYUNDAI	PSF-3	**SUBARU**	PS FLUID
KIA	PSF-III	**TOYOTA**	008886-01
MAZDA	PSF	**TOYOTA**	PSF-EH
MITSUBISHI	DIAMOND PSF-2M		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.5
Viscosity index	ASTM D2270		180
Pour point	ASTM D6892	°C	-52
Flash Point COC	ASTM D92	°C	186
Colour	VISUAL		YELLOW

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

The CHAMPION brand and design are registered trademarks of Champion Chemicals NV – Made in Belgium