

# WOLF ANTI-FREEZE LONGLIFE G12+

14/04/2025  
50001

An undiluted on ethylene glycol based coolant concentrate for use in engines. It employs Organic Acid Technology (OAT) inhibitor and is nitrite, amine and phosphate (NAP) free. It is also free of borate and silicate. The sophisticated technology provides superior and permanent protection to all components of the cooling system and a life span of 4 - 6 years or 250.000 km for passenger cars and 500.000 km for professional applications.

## APPLICATIONS

Formulated for long-term use in all engines especially those constructed from aluminium, cast iron and magnesium alloys. Not the best choice for older cooling systems that have copper/brass radiators and heater cores, especially not for the lead solder used in them. Suitable when diluted for cooling circuits of the open or closed type (vehicles and heating). Advised to dilute with demineralised water. Protection temperature: -16 °C needs 30% AF // -22 °C needs 40% AF // -36 °C needs 50% AF.

## FEATURES

Anti-freeze properties: Superior cold temperature performance

Anti-corrosion properties: Outstanding corrosion protection

Total system protection: Excellent heat transfer and dispersion

## SPECIFICATIONS

|                 |             |     |          |
|-----------------|-------------|-----|----------|
| AFNOR           | NF R 15-601 | MAN | 324 SNF  |
| ASTM            | D3306       | MB  | 325.2    |
| ASTM            | D4985       | MB  | 325.3    |
| BS              | 6580        | MTU | MTL 5048 |
| POLISH STANDARD | PN-C-40007  | VW  | TL 774-D |
| SAE             | J1034       | VW  | TL 774-F |
| DTFR            | 29C110      |     |          |

## TYPICAL CHARACTERISTICS

| Test                       | Method     | Unit        | Average results |
|----------------------------|------------|-------------|-----------------|
| Freezing point 50% vol. AF | ASTM D1177 | °C          | -36             |
| Reserve alkalinity         | ASTM D1121 | ml 0.1M HCl | 6.5             |
| Density at 20°C            | ASTM D4052 | g/ml        | 1.117           |
| Colour                     | VISUAL     |             | PINK            |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

