

WOLF EXTENDTECH 80W90 LS GL 5

02/03/2026
2408

Mineral oil composed of paraffinic base oils and selected additives based on sulfur-phosphorus. A special friction additive emparts to this oil the necessary properties to be used in differentials, which are equipped with a "limited-slip" mechanism.

APPLICATIONS

This oil is mainly used in all hypoid rear axles with a limited-slip mechanism.

FEATURES

Frictional properties: easy shift performance
Anti-wear protection: long transmission life
Extended oil life: proven resistance to oil degradation

SPECIFICATIONS

API	GL-5	ZF	TE-ML 07A
MIL	L-2105 C	ZF	TE-ML 08
MIL	L-2105 D		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.897
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	145
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.4
Viscosity index	ASTM D2270		97
Pour point	ASTM D6892	°C	-30
Brookfield viscosity at -26 C	ASTM D2983	mPa.s	130000
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.