

CHAMPION AGRILINE BIOCHAIN

Quickly biodegradable product, which is composed of vegetable oils and toxicologically neutral components, which are absorbed by micro-organisms in the shortest possible time. It presents an exceptional viscosity/temperature relation and a very good stability at low temperatures. It has a remarkable adhesive power for this type of product.

APPLICATIONS

This product is mainly used as a biodegradable lubricant for chain saws.

FEATURES

Biodegradability: vegetable oil, quick decomposition

Stickiness: strong adhesive power

SPECIFICATIONS

ISO 68 CEC L-33-T-82

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.912
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	69
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.6
Viscosity index	ASTM D2270		204
Pour point	ASTM D6892	°C	-21
Flash Point COC	ASTM D92	°C	>200
Colour	VISUAL		GREEN
Biodegradability	CEC L-33-T-82	%	>90

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

