

WOLF VITALTECH MULTI VEHICLE ATF

03/04/2026
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

IDEMITSU	K17	CHRYSLER	05127382AA
JASO	M315, Class 1A	CHRYSLER	AS68RC ATF
AISIN-WARNER	AW-1	CHRYSLER	ATF +3 AND +4
AISIN-WARNER	JWS 3309	CHRYSLER	MD 7176E
AISIN-WARNER	JWS 3314	CHRYSLER	MS 9602
AISIN-WARNER	JWS 3317	DTFR	13C100
ALFA ROMEO	HP20	DTFR	13C110
ALLISON	C4	DTFR	13C120
ALLISON	TES 295	DTFR	13C140
ALLISON	TES 389	DTFR	13C150
BENTLEY	PY112995PA	DTFR	13C170
BMW	81 22 9 400 275	DTFR	13C180
BMW	81 22 9 401 220	DTFR	38B100
BMW	83 22 0 024 359	FIAT	9.55550-AV1
BMW	83 22 0 026 922	FIAT	9.55550-AV4
BMW	83 22 0 142 516	FORD	ESP-M2C138-CJ
BMW	83 22 0 403 248	FORD	ESP-M2C166-H
BMW	83 22 0 403 249	FORD	M2C-202B
BMW	83 22 2 152 426	FORD	MERCON
BMW	83 22 2 344 206	FORD	MERCON V
BMW	83 22 2 355 599	FORD	WSS-M2C195-A
BMW	83 22 9 407 765	FORD	WSS-M2C919-E
BMW	83 22 9 407 807	FORD	WSS-M2C922-A1
BMW	ATF 3	FORD	WSS-M2C924-A
BMW	ATF 4	GM	1940700
BMW	ATF 6	GM	1940767
BMW	ETL 7045E	GM	210005966
BMW	ETL 8072B	GM	22717466
BMW	LA 2634	GM	88900925
BMW	LT 71141	GM	9986195
BMW	ZF 5HP18FL,5HP24,5HP30	GM	DEXRON II

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



GM	DEXRON II-D	MITSUBISHI	ATF J2
GM	DEXRON II-E	MITSUBISHI	Diaqueen ATF MA1
GM	DEXRON III	MITSUBISHI	Diaqueen ATF-PA
GM	DEXRON III-G	MITSUBISHI	Diaqueen J3
GM	DEXRON III-H	MITSUBISHI	Diaqueen SK
GM	DEXRON TYPE A, SUFFIX A	MITSUBISHI	Diaqueen SP-II
HONDA	ATF Z-1	MITSUBISHI	Diaqueen SP-III
HONDA	Premium	MITSUBISHI	Diaqueen SP-IV
HYUNDAI	SFU	MITSUBISHI	SFU
HYUNDAI	SP-II	MITSUBISHI	V5AWF
HYUNDAI	SP-III	MOPAR	ATF +3
ISUZU	BESCO ATF-II	MOPAR	ATF +4
ISUZU	BESCO ATF-III	NISSAN	999MP-ATFD3MP
ISUZU	Genuine	NISSAN	D3m
ISUZU	PSF	NISSAN	MATIC-D
ISUZU	SCS Fluid	NISSAN	MATIC-J
JAGUAR	ATF 3403 M115	NISSAN	MATIC-K
JAGUAR	Fluid 8432	NISSAN	MATIC-W
JAGUAR	JLM 20238	OPEL	GM 1940700
JAGUAR	JLM 20292 (LA 3403-M115)	OPEL	GM 1940767
JAGUAR	JLM 21044	OPEL	GM 21005966 Transaxle
JEEP	ATF 3	OPEL	GM 2217466
KIA	ATF Red -1K	OPEL	GM 9986185
KIA	SP-II	PORSCHE	000.043.202.28
KIA	SP-III	PORSCHE	000.043.204.63
LAND ROVER	LR002748	PORSCHE	000.043.205.09
LAND ROVER	N402	PORSCHE	999.917.547.00(A2)
MAN	339 V1/Z1	PORSCHE	JWS 3309 (Cayenne)
MAN	339 V2/Z2	PORSCHE	LA 3403-M115
MAN	339 Z3	PORSCHE	T-IV (JWS 3309)
MASERATI	231603	PSA	P/N Z 000169756
MAZDA	ATF 3317	PSA	ZF 4HP20
MAZDA	ATF D-II	RENAULT	A14
MAZDA	ATF F-1	RENAULT	DPO/AL4
MAZDA	ATF FZ	RENAULT	MATIC-D2
MAZDA	ATF M-III	RENAULT	Samsung SATF-D
MAZDA	ATF M-V (Type M5)	SAAB	T-IV (JWS 3309)
MAZDA	ATF N-1	SAAB	Transmax J- TIV
MAZDA	ATF S-1	SCION	T-II
MB	236.1	SCION	T-III
MB	236.10	SCION	T-IV
MB	236.11	SUBARU	ATF 5AT
MB	236.12	SUBARU	ATF, ATF HP
MB	236.14	SUBARU	K0140Y0700
MB	236.2	SUZUKI	AT OIL 5D06
MB	236.3	SUZUKI	ATF 2324K
MB	236.5	SUZUKI	ATF 2326
MB	236.6	SUZUKI	ATF 3310
MB	236.7	SUZUKI	ATF 3311
MB	236.8	SUZUKI	ATF JWS 3309
MB	236.9	SUZUKI	Dexron III
MB	236.91	TOYOTA	TYPE T-II
MINI	83 0 402 42	TOYOTA	TYPE T-III
MINI	T-IV	TOYOTA	TYPE T-IV
MITSUBISHI	4030401	VOITH	55.6335(G607. G1363)

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



VOITH	DIWA #013S	VW	TL 52 162
VOLVO Constr. Equip. (VCE)	1273,41	VW	TL 5612
VOLVO	1161540	ZF	TE-ML 02F
VOLVO	97325	ZF	TE-ML 03D
VOLVO	JWS 3309	ZF	TE-ML 04D
VW	G 052 025	ZF	TE-ML 09
VW	G 052 055	ZF	TE-ML 11A
VW	G 052 162	ZF	TE-ML 11B
VW	G 052 533	ZF	TE-ML 14A
VW	G 052 990	ZF	TE-ML 14B
VW	G 055 025	ZF	TE-ML 14C
VW	G 055 540	ZF	TE-ML 16L
VW	G 060 162	ZF	TE-ML 17C
VW	G US 000 162		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

