

CHAMPION **ECO FLOW** MULTI VEHICLE ATF FE

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration

Anti-wear protection: significantly extended transmission life

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

AIISIN-WARNER	AW-1	HYUNDAI	NWS-9638 T5
AIISIN-WARNER	AW-2	HYUNDAI	SPH-IV
AIISIN-WARNER	JWS 3324	HYUNDAI	SP-IV
ALLISON	C4	ISUZU	WSI
BMW	000 043 306 24	JAGUAR	02JDE26444
BMW	83 22 0 397 114	LAND ROVER	LR023288
BMW	83 22 2 305 397	MAZDA	FZ
BMW	83 22 9 407 858	MB	236.12
BMW	83222152426	MB	236.14
BMW	83222167718	MB	236.41
BMW	83222413477	MITSUBISHI	ATF J3
BMW	958 300 540 00	MITSUBISHI	Diaqueen ATF PA
BMW	ATF 3	NISSAN	MATIC-S
BMW	ATF 6	PSA	1635056080
BMW	ATF 7	TESLA	ATF9/EDF2
BMW	L 12108	TOYOTA	AUTO FLUID WS
BMW	M-1375.4	VOLVO	31492172
CHRYSLER	68157995AA	VOLVO	31492173
FIAT	9.55550-AV2	VW	G 053 001
FIAT	9.55550-AV5	VW	G 055 005
FORD	MERCON LV	VW	G 055 162
FORD	MERCON SP	VW	G 055 540
FORD	WSS-M2C195-A	VW	G 060 162
FORD	WSS-M2C924-A		
FORD	WSS-M2C938-A		
GM	DEXRON HP		
GM	DEXRON VI		
HONDA	DPSF		
HONDA	DPSF2		
HONDA	DW-1		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.45
Viscosity index	ASTM D2270		156
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

