

CHAMPION OEM SPECIFIC 5W30 UHPD

This is a full synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. The formulation includes a state of the art friction modifier for improved fuel economy.

APPLICATIONS

It is recommended for Euro V and most Euro VI engines. Perfectly compatible with all after-treatment systems and devices (EGR, SCR, DPF, etc.) in combination with low sulfur diesel (max 50 ppm).

FEATURES

Aftertreatment protection: full aftertreatment system protection

Fuel economy: superior fuel economy and CO₂ reduction

Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

ACEA	E4-16
ACEA	E6-16
ACEA	E7-16
ACEA	E9-16
API	CJ-4
API	SN
JASO	DH-2
CATERPILLAR	ECF-3
CUMMINS	CES 20081
DETROIT DIESEL	DFS 93K218
DEUTZ	DQC IV-10 LA
MACK	EO-M PLUS
MACK	EO-N Premium Plus
MACK	EO-O Premium Plus
MAN	M3271-1
MAN	M3477
MAN	M3575
MAN	M3677
MAN	M3691
MB	235.28
MTU	Oil Category 2.1
MTU	Oil Category 3.1
RENAULT	RGD
RENAULT	RLD-2
RENAULT	RLD-3
RENAULT	RXD
SCANIA	LDF-4
VOITH	Retarder Oil Class B
VOLVO	CNG
VOLVO	VDS-3
VOLVO	VDS-4

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.8
Viscosity index	ASTM D2270		168
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	12.8
Pour point	ASTM D6892	°C	-51
CCS viscosity at -30°C	ASTM D5293	mPa.s	5640
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

