

CHAINSAW OIL EXTRA

14/04/2025
29081

This is a very strongly adhesive oil based on mineral oils and an adhesion improver. It was specifically developed for the lubrication of chainsaws, where high demands are made. Warning : never use in the engine.

APPLICATIONS

It is used primarily for the lubrication of chains saws. Due to its excellent adhesion ability it can also be used for the lubrication of conveyor chains and textile machinery.

FEATURES

Stickiness: strong adhesive power

SPECIFICATIONS

ISO 6743/1

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	180
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	16.5
Viscosity index	ASTM D2270		96
Pour point	ASTM D6892	°C	-9
Flash Point COC	ASTM D92	°C	265

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION