

25/09/2026 / 13125

CHAMPION AGRILINE 4T 10W30

This is a low viscosity engine oil for gasoline and diesel engines. It combines good fluidity at low temperature with low ash content, while maintaining excellent detergent and dispersant properties.

KÄYTTÖKOHTEET

Used for the lubrication of light gasoline and diesel engines, which prefer this viscosity class. Particularly suitable for 4T- auxilliary engines and horticulture material (e.g. Honda).

OMINAISUUDET

Moottorin suojaus: erinomainen moottorin suojaus ja puhtaus
Lämpötilakestävyys: korkea viskositeetin stabiilisuus

LUOKITUKSET

ACEA	A2	**API**	SJ/CF
ACEA	B2	**JASO**	MA

TYYPILLISET OMINAISUUDET

Testi	Menetelmä	Yksikkö	Keskimääräinen tulos
Tiheys lämpötilassa 15 °C	ASTM D4052	g/ml	0.879
Kinemaattinen viskositeetti lämpötilassa 40 °C	ASTM D445	mm²/s	71.7
Kinemaattinen viskositeetti lämpötilassa 100 °C	ASTM D445	mm²/s	11.1
Viskositeetti-indeksi	ASTM D2270		146
B.N. (HCLO4-menetelmä)	ASTM D2896	mg KOH/g	10.9
Jähmepiste	ASTM D6892	°C	-33
CCS-viskositeetti lämpötilassa -25 °C	ASTM D5293	mPa.s	6500
Sulfaattituhka	ASTM D874	Mass %	0.7
Leimahduspiste (COC)	ASTM D92	°C	215

Pidätämme oikeuden muuttaa tuotteidemme yleisominaisuuksia, jotta asiakkaamme voivat hyödyntää uusimpia teknisiä uudistuksiamme.

CHAMPION CHEMICALS NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

The CHAMPION brand and design are registered trademarks of Champion Chemicals NV – Made in Belgium