

WOLF GUARDTECH ATF D

14/04/2025
3001

This is an oil, with a high viscosity index, especially designed to satisfy the requirements of General Motors for the use in the first generation of automatic transmissions. Very good anti-wear and detergent qualities, anti-foam and anti-corrosion.

APPLICATIONS

This oil is used in automatic transmissions, power steering, torque convertors and hydraulic systems.

FEATURES

Anti-wear protection: long transmission life
Extended oil life: optimized thermal and oxidation stability

SPECIFICATIONS

DIN	HLP-D	DTFR	13C120
ALLISON	C2/C3	GM	6032-M DEXRON
ATF	TYPE A SUFFIX A	MB	236.2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm²/s	37.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.6
Viscosity index	ASTM D2270		179
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	2.1
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	50.000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.