

WOLF OFFICIALTECH 10W40 S3

30/01/2026
1727

This is a semi synthetic lubricant based on carefully selected very high quality base oils. This "long-drain" oil is engineered to provide outstanding lubrication to modern, high performance diesel engines.

APPLICATIONS

This oil is suitable for Euro IV and Euro V engines. Due to the high ash content, this oil is not suitable for most engines and vehicles equipped with a particulate filter.

FEATURES

Emission compatibility: superior emission reduction
Total engine protection: outstanding engine cleanliness and durability
Cold start: very good fluidity at low temperature

SPECIFICATIONS

ACEA	E4	MAN	M3377
ACEA	E7	MB	229.1
API	CF-4	MB	235.28
API	CG-4	MTU	Oil Category 1
API	CH-4	MTU	Oil Category 2
API	CI-4/SL	MTU	Oil Category 3
JASO	DH-1	RENAULT	approval RLD-2
ALLISON	C4	RENAULT	RLD
CATERPILLAR	ECF-1a	RENAULT	RXD
CATERPILLAR	ECF-2	SCANIA	approval LDF-3
CATERPILLAR	TO-2	SCANIA	LDF-2
CUMMINS	CES 20072	VOITH	Retarder Oil Class A
CUMMINS	CES 20076	VOITH	Retarder Oil Class B
CUMMINS	CES 20077	VOLVO	approval VDS-3
CUMMINS	CES 20078		
DAF	EXTENDED DRAIN		
DETROIT DIESEL	DFS 93K215		
DEUTZ	DQC-III-10		
DEUTZ	DQC-III-18		
DTFR	13D100		
DTFR	13D110		
DTFR	15B110		
DTFR	15B120		
GLOBAL	DHD-1		
IVECO	18-1804 Classe T2 E7		
IVECO	18-1804 Classe T3 E4		
MACK	approval EO-N		
MACK	EO-M PLUS		
MACK	EO-N Premium Plus		
MAN	M3275-1		
MAN	M3277		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	86.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.3
Viscosity index	ASTM D2270		155
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	16.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.9
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

