

CHAMPION MOTO HP 4T 20W50 MULTI

This four-stroke motorcycle engine oil guarantees a smooth and stable ride. The lubricant's high viscosity at high temperatures ensures complete engine protection in hot riding conditions.

APPLICATIONS

This lubricant is developed for the engines, transmissions and wet clutches of four-stroke motorcycles. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Engine protection: extended motorcycle lifespan.

Simpler fluid management thanks to the broad applicability.: Simpler fluid management thanks to the broad applicability.

SPECIFICATIONS

API SG/CD JASO MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.886
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	159
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.1
Viscosity index	ASTM D2270		127
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	5.9
Pour point	ASTM D6892	°C	-36

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

