

CHAMPION COMPETE

ISO 68

This mineral fluid stabilises the hydraulic performance with its formulation with anti-wear and anti-corrosion additives. This product may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Can be used in a range of different demanding hydraulic systems. It is adapted to meet the DIN 51524 Part 1 specification.

FEATURES

Anti-wear and oxidation stability: superior protection.
Anti-foam properties: excellent anti-foam properties.

SPECIFICATIONS

DIN	51524 Part 2	ISO	6743-4, HM
ISO	11158, HM		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.6
Viscosity index	ASTM D2270		102
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 3 870 00 00
www.championlubes.com

