

CHAMPION COMPETE SN/CF 5W40

This is a full synthetic lubricant to meet the strict requirements of manufacturers. This oil provides an excellent fluidity at low temperatures, a very low resistance when starting and a very high thermal stability.

APPLICATIONS

This oil is used in gasoline and diesel engines with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

FEATURES

Drain interval extension: extended oil drain interval.

SPECIFICATIONS

ACEA	A3/B3-16	MB	229.1
ACEA	A3/B4	VW	502 00
API	SN/CF	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	80.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		178
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	1.1
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

