

CHAMPION PROPULSE TT 4T 10W40 ESTER

This synthetic blend contains groundbreaking additive technology and ester-based base oils. This lubricant increases both engine performance and protects all lubricated parts completely. This powerful formulation covers a large part of the motorcycle market thanks to its high-end properties.

APPLICATIONS

This four-stroke motorcycle engine oil exceeds the standards of API SN, SM, SL, SJ, SH and SG. It surpasses the requirements set by different manufacturers.

FEATURES

Extended wear protection: improved engine, transmission & wet clutch performance

Riding comfort: recommended product for touring & daily riding

Applicability: easier fluid management thanks to the oil's broad applicability

SPECIFICATIONS

API SN JASO approval MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	95
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.9
Viscosity index	ASTM D2270		165
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	7.3
Pour point	ASTM D6892	°C	-45
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

