

CHAMPION COOLANT G11 GREEN -17°C

A diluted on ethylene glycol based coolant for use in engines. It employs Inorganic Acid Technology (IAT) inhibitor and is borate, nitrite, amine and phosphate (NAP) free and includes silicate. This sophisticated technology eliminates the formation of silicate gel which is observed with inferior products. Ready to use solution.

APPLICATIONS

Formulated for use in all engines operating in hot weather conditions, including those constructed from aluminium alloys. Best choice for cooling systems that have copper/brass radiators and heater cores, especially for the lead solder used in them. Suitable for cooling circuits of the open or closed type (vehicles and heating) with a protection against freezing until -17°C.

This solution is ready to use and can be used during the whole year.

FEATURES

Anti-freeze properties: superior cold temperature performance

Anti-corrosion properties: outstanding corrosion protection

Total system protection: excellent heat transfer and dispersion.

SPECIFICATIONS

AFNOR	NF R 15-601	FORD	SSM-97B9102A
ASTM	D3306	GM	B 0400240
ASTM	D4985	GME	13368
BS	6580	MAN	324 NF
POLISH STANDARD	PN-C-40007	MB	325.0
SAE	J1034	MTU	MTL 5048
BMW	N600.69.0	SAAB	690 1599
DAVID BROWN	DBL-7700	SCANIA	S28917.3
DTFR	29C100	SCANIA	TB 145
FIAT	55523/1	VW	TL 774-C [G11]

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
pH	ASTM D1287		8.1
Density at 20°C	ASTM D4052	g/ml	1.054
Colour	VISUAL		GREEN
Freezing point [refracto]	ASTM D3321	°C	-17
Water content	ASTM D1123	% wt/wt	66.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

