

WOLF AROWEP ISO 1000

02/03/2026
4114

This is an extreme pressure oil for industrial gears. The paraffinic character of the base oil ensures an excellent course of the viscosity/temperature curve and a high resistance against oxidation and ageing. The favorable property of mineral base oil is further strengthened by the addition of appropriate additives. The high pressure additives based on sulfur and phosphorus compounds form a chemical film on tooth surfaces and as such prevents wear and a noticeable reduction in friction. Special anti-corrosion and anti-foam additives complete the composition of this oil.

KÄYTTÖKOHTTEET

This oil is recommended for the lubrication of gearboxes (lubrication by oil bath, oil mist or oil circulation) and it is specifically suitable for heavy loads and high temperature.

OMINAISUUDET

Extreme pressure properties: superior EP properties
Anti-wear and oxidation stability: adequate protection of systems

LUOKITUKSET

AGMA	9005-E02	ISO	12925-1 CKC
AISE	224	ISO	12925-1 CKD
DIN	51517 CLP	DAVID BROWN	S1.53.101E

TYYPILLISET OMINAISUUDET

Testi	Menetelmä	Yksikkö	Keskimääräinen tulos
Tiheys lämpötilassa 15 °C	ASTM D4052	g/ml	0.900
Kinemaattinen viskositeetti lämpötilassa 40 °C	ASTM D445	mm ² /s	975
Kinemaattinen viskositeetti lämpötilassa 100 °C	ASTM D445	mm ² /s	51.0
Viskositeetti-indeksi	ASTM D2270		98
A.N. (kolorimetrisen)	ASTM D974	mg KOH/g	0.38
Jähmepiste	ASTM D6892	°C	-2
Leimahduspiste (COC)	ASTM D92	°C	265
F Z G -testi	DIN 51354		12

Pidätämme oikeuden muuttaa tuotteidemme yleisominaisuuksia, jotta asiakkaamme voivat hyödyntää uusimpia teknisiä uudistuksiamme.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

