

WOLF ECOTECH CVT FLUID

30/10/2025
3020

This is a full synthetic lubricant based on carefully selected very high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

AUDI	TL 52116	FORD	XT-7-QCFT
AUDI	TL 52180	FUJIIYUUKO	i-CVTF FG
AUDI	TL 52516	GEELEY	CVTF-EX1
BMW	83 22 0 136 376	GM	1940713
BMW	83 22 0 429 154	GM	1940714
BMW	83 22 2 344 207	GM	CVTF GREEN 2/SATURN DEX-CVT
BMW	ATF 5	GM	DEX-CVT
BMW	EZL799/EZL799A	GM	HP CVTF 95529854
CHERY	CVT	GM	VT 40
CHERY	WCF-1	HONDA	08200-9006
CHRYSLER	CVTF+4	HONDA	0826099905HE
CHRYSLER	NS 2	HONDA	087009006
CITROËN	9735 EF	HONDA	CVT-F
DAIHATSU	AMIX CVTF DFC	HONDA	HCF-2/HMMF (No Start Clutch)
DAIHATSU	AMIX CVTF DFE	HONDA	Ultra HEVF-Type 1
DAIHATSU	AMIX CVTF DTC	HYUNDAI	CVT-1
DAIHATSU	AMIX CVTF-DC	HYUNDAI	Genuine CVT
DAIHATSU	CVTF 3320	HYUNDAI	SP III (CVT models only)
DAIHATSU	FLUID TC	HYUNDAI	SP-CVT1
DODGE	05191184AA	INFINITI	NS-1, NS-2, NS-3
DODGE	NS-2/CVTF+4	JEEP	05191184AA
DS	9735 EF	JEEP	NS-2/CVTF+4
FORD	CVT23	KIA	SP-CVT 1
FORD	CVT30	LEXUS	CVT FE
FORD	MERCON C	LEXUS	CVTF 3320
FORD	WSS-M2C928-A	LEXUS	Fluid FE
FORD	WSS-M2C933-A	LEXUS	Fluid TC

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



LIFAN	CVT	SUBARU	i-CVTF
MAZDA	CVTF 3320	SUBARU	i-CVTF FG
MB	236.20/CVT28	SUBARU	Lineartronic CV-30
MINI	EZL799/EZL799A/CVT V1	SUBARU	Lineartronic CVTF II
MITSUBISHI	CVTF ECO J4	SUZUKI	CVTF 3320
MITSUBISHI	CVTF J-1	SUZUKI	CVTF 4401
MITSUBISHI	CVTF J-4	SUZUKI	CVTF GREEN 2
MITSUBISHI	CVTF J-4+	SUZUKI	NS-2/SHELL GREEN 1 V
NISSAN	NS-1/NS-2/NS-3/Matic W	TOYOTA	CVT FE
PUNCH	EZL799/EZL799A	TOYOTA	TC
RENAULT	CVT CK/SK/FK	VOLVO	CVT 4959
RENAULT	ELFMATIC	VW	G 052 180
SUBARU	e-CVTF	VW	G 052 516
SUBARU	High Torque CVTF		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm²/s	32.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.1
Viscosity index	ASTM D2270		187
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	10600
Flash Point COC	ASTM D92	°C	188
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.